

Stormwater
Management
Manual for
Western Australia

11
Further
Information



Department of Water
Government of Western Australia

Cover photograph: Participants in a training course practising how to clean up spills at commercial and industrial sites, to prevent stormwater and site contamination. (Source: Perth Petroleum Services.)

Stormwater Management Manual for Western Australia

11 Further Information

Prepared by Emma Monk and Tania Liaghati, Department of Water
Consultation and guidance from the Stormwater Working Team



Department of **Water**
Government of **Western Australia**

June 2007

Acknowledgments

This chapter was prepared by Emma Monk and Tania Liaghati, Department of Water. Sincere thanks to everyone that provided comments, particularly the following people who provided considerable information or feedback: Parsons Brinckerhoff; Rachel Spencer and Peter Adkins - Swan River Trust; Stephen Wong - Department of Environment and Conservation; Bill Till, Verity Klemm and Greg Davis - Department of Water.

Stormwater Working Team

Organisation

Conservation Council of Western Australia
Department for Planning and Infrastructure
Department of Environment and Conservation
Department of Environment and Conservation
Department of Health
Department of Water
Eastern Metropolitan Regional Council
Housing Industry Association
Institute of Public Works Engineering Australia
Institution of Engineers Australia
LandCorp
Main Roads Western Australia
Swan Catchment Council
Swan River Trust
Urban Development Institute of Australia
Water Corporation
Western Australian Local Government Association

Representative

Mr Steven McKiernan
To be advised (Ken Dawson is the proxy)
Ms Justine Lawn
Mr Stephen Wong
Dr Michael Lindsay
Mr Greg Davis
Ms Colleen Murphy
Ms Sheryl Chaffer
Mr Martyn Glover
Mr Sasha Martens
Mr Bruce Low
Mr Jerome Goh
Ms Patricia Pedelty
Ms Rachel Spencer
Mr Anthony McGrath
Mr Michael Thurner
Mr Michael Foley

Reference details

The recommended reference for this publication is:

Department of Water 2007, *Further Information, Stormwater Management Manual for Western Australia*, Department of Water, Perth, Western Australia.

ISBN 1-92084-954-8 [Print - Manual]

June 2007

An electronic version of this chapter is available at <<http://stormwater.water.wa.gov.au>>

Preface

A growing public awareness of environmental issues in recent times has elevated water issues to the forefront of public debate in Australia.

Stormwater is water flowing over ground surfaces and in natural streams and drains as a direct result of rainfall over a catchment (ARMCANZ and ANZECC, 2000).

Stormwater consists of rainfall runoff and any material (soluble or insoluble) mobilised in its path of flow. Stormwater management examines how these pollutants can best be managed from source to the receiving water bodies using the range of management practices available.

In Western Australia, where there is a superficial aquifer, drainage channels can commonly include both stormwater from surface runoff and groundwater that has been deliberately intercepted by drains installed to manage seasonal peak groundwater levels. Stormwater management is unique in Western Australia as both stormwater and groundwater may need to be managed concurrently.

Rainwater has the potential to recharge the superficial aquifer, either prior to runoff commencing or throughout the runoff's journey in the catchment. Urban stormwater on the Swan Coastal Plain is an important source of recharge to shallow groundwater, which supports consumptive use and groundwater dependent ecosystems.

With urban, commercial or industrial development, the area of impervious surfaces within a catchment can increase dramatically. Densely developed inner urban areas are almost completely impervious, which means less infiltration, the potential for more local runoff and a greater risk of pollution. Loss of vegetation also reduces the amount of rainfall leaving the system through the evapo-transpiration process. Traditional drainage systems have been designed to minimise local flooding by providing quick conveyance for runoff to waterways or basins. However, this almost invariably has negative environmental effects.

This manual presents a new comprehensive approach to management of stormwater in WA, based on the principle that stormwater is a RESOURCE – with social, environmental and economic opportunities. The community's current environmental awareness and recent water restrictions are influencing a change from stormwater being seen as a waste product with a cost, to a resource with a value. Stormwater Management aims to build on the traditional objective of local flood protection by having multiple outcomes, including improved water quality management, protecting ecosystems and providing livable and attractive communities.

This manual provides coordinated guidance to developers, environmental consultants, environmental/community groups, Industry, Local Government, water resource suppliers and State Government departments and agencies on current best management principles for stormwater management.

Production of this manual is part of the Western Australian Government's response to the State Water Strategy (2003).

It is intended that the manual will undergo continuous development and review. As part of this process, any feedback on the series is welcomed and may be directed to the Drainage and Waterways Branch of the Department of Water.

Western Australian Stormwater Management Objectives

Water Quality

To maintain or improve the surface and groundwater quality within the development areas relative to pre development conditions.

Water Quantity

To maintain the total water cycle balance within development areas relative to the pre development conditions.

Water Conservation

To maximise the reuse of stormwater.

Ecosystem Health

To retain natural drainage systems and protect ecosystem health .

Economic Viability

To implement stormwater management systems that are economically viable in the long term.

Public Health

To minimise the public risk, including risk of injury or loss of life, to the community.

Protection of Property

To protect the built environment from flooding and waterlogging.

Social Values

To ensure that social, aesthetic and cultural values are recognised and maintained when managing stormwater.

Development

To ensure the delivery of best practice stormwater management through planning and development of high quality developed areas in accordance with sustainability and precautionary principles.

Western Australian Stormwater Management Principles

- Incorporate water resource issues as early as possible in the land use planning process.
- Address water resource issues at the catchment and sub-catchment level.
- Ensure stormwater management is part of total water cycle and natural resource management.
- Define stormwater quality management objectives in relation to the sustainability of the receiving environment.
- Determine stormwater management objectives through adequate and appropriate community consultation and involvement.
- Ensure stormwater management planning is precautionary, recognises inter-generational equity, conservation of biodiversity and ecological integrity.
- Recognise stormwater as a valuable resource and ensure its protection, conservation and reuse.
- Recognise the need for site specific solutions and implement appropriate non-structural and structural solutions.

Contents

1 Introduction	1
1.1 Aim of the further information chapter.....	1
2 Glossary	1
3 Contacts	10
4 Websites	10
5 Glossary references	12
6 Further reading	13
7 Acronyms	14

THIS PAGE HAS BEEN LEFT BLANK INTENTIONALLY

1 Introduction

1.1 Aim of the further information chapter

The aim of this chapter is to provide a glossary of terms used in the manual and some useful contacts, websites and references for obtaining further information about stormwater management.

2 Glossary

- **Adaptive environmental management:** A type of environmental management where the approach to managing water resources in urban areas will evolve over time as new ideas, information, drivers for change and technologies emerge.
- **Adsorption:** The adhesion of a substance to the surface of a solid or liquid; often used to extract contaminants by causing them to be attached to adsorbents such as activated carbon or silica gel. Hydrophobic or water repulsing adsorbents are used to extract oil from waterways when oil spills occur. Heavy metals such as zinc and lead and nutrients such as phosphorus often adsorb onto sediment.
- **Aeration:** The injection of air through diffusers into water bodies, or rapid mixing (e.g. via riffles) of the surface of water bodies to promote transfer of atmospheric air into the water column. A treatment process adopted in situations of high loading of oxygen demanding substances. (ARMCANZ & ANZECC 2000.)
- **Aerobic or oxic zone:** An environment in which there is free oxygen (ARMCANZ & ANZECC 2000).
- **Anaerobic or anoxic zone:** An environment devoid of oxygen (ARMCANZ & ANZECC 2000).
- **Aquifer:** A geological formation or group of formations capable of receiving, storing and transmitting significant quantities of water (Water and Rivers Commission 2000a).
- **Armouring or stabilisation:** The use of rock, geotextile and/or vegetation to bind the soil forming the bank or bed of channels such as to resist erosion by elevated flow velocities (ARMCANZ & ANZECC 2000).
- **Atmospheric deposition:** Contaminants accumulating across urban surfaces as a result of deposition of fine airborne solids (ARMCANZ & ANZECC 2000).
- **At-source controls:** Non-structural or structural best management practices implemented at the site where stormwater runoff is created, to minimise the generation of excessive stormwater runoff and/or pollution of stormwater.
- **Attenuation:** The reduction in the magnitude of flows, concentrations or loads of contaminants (ARMCANZ & ANZECC 2000).
- **Average recurrence interval (ARI):** ARI is defined as the average, or expected, value of the periods between exceedances of a given rainfall total accumulated over a given duration. ARI events can be grouped into:
 - Small: Less than and up to 1 year ARI events ($x < 1$ year ARI events).
 - Minor: Greater than 1 year and less than 10 year ARI events ($1 \text{ year} < x < 10$ year ARI events).
 - Major: 10 year to 100 year ARI events (10 – 100 year ARI events).
 - Extreme: Greater than 100 year ARI events ($x > 100$ year ARI events).
- **Bankfull flow:** The dominant channel forming discharge (Water and Rivers Commission 2001). The flow rate at which a channel is filled from bank to bank. The frequency of bankfull conditions is commonly adopted as the criterion for maintaining the channel cross-section and freedom from sedimentation in the longer term. This frequency will vary according to climatic regions (ARMCANZ & ANZECC 2000), but usually occurs once every 1.5 years.
- **Bank stabilisation:** See ‘armouring or stabilisation’.

- **Baseflow:** The underlying flow rate that cannot be directly attributed to storm events (ARMCANZ & ANZECC 2000). The part of the total flow in a water body derived from groundwater discharge (Department of Environment 2003).
- **Best management practices (BMPs):** Devices, practices or methods for removing, reducing, retarding or preventing targeted stormwater runoff constituents, pollutants and contaminants from reaching receiving waters (Taylor & Wong 2002) and for reducing the volume of stormwater runoff.
- **Biochemical oxygen demand (BOD):** The oxygen consumption (respiration) resulting from bacterial breakdown of organic material, or as a result of some inorganic oxygen reducing species (ammonia) (ARMCANZ & ANZECC 2000).
- **Biodiversity:** The variability among living organisms from all sources (including terrestrial, marine and other aquatic ecosystems and the ecological complexes of which they are part) and the diversity within and between species and of ecosystems (ARMCANZ & ANZECC 2000).
- **Biofilm:** A gelatinous sheath of algae and micro-organisms, including benthic algae and bacteria, formed on surfaces such as gravel, sediment and plants (ARMCANZ & ANZECC 2000).
- **Bioretention:** A stormwater management device that consists of an excavated basin or trench that is filled with porous media and planted with vegetation.
- **Bore:** A narrow, lined hole drilled to withdraw or monitor groundwater.
- **Brownfield:** Areas of land that have been developed into urban land uses.
- **Buffer strip:** Areas of vegetation through which runoff passes while travelling to a discharge point and which are therefore aligned perpendicular to the direction of flow.
- **Capacity building program:** A holistic approach to knowledge building and transfer, which fosters skill development, competency, innovation and confidence. It is also a means to facilitate network building, linkages and training for continuous improvement.
- **Catchment:** A topographically defined area draining surface water to a single outlet point.
- **Channel:** The bed and banks of a stream or constructed drain (ARMCANZ & ANZECC 2000) that carries all flows except floods.
- **Clay (soils):** A fine-grained mineral soil consisting of particles less than 0.002 mm in equivalent diameter (Charman & Murphy 1991).
- **Colloids:** Fine abiotic and biotic particles of typically 0.1 μm to 1 nm in diameter (ARMCANZ & ANZECC 2000).
- **Compaction:** Any process whereby the density of soils is increased. This process results in lower permeability and poorer soil aeration. (Charman & Murphy 1991.)
- **Constructed wetland:** A vegetated detention area designed and built to remove contaminants from stormwater runoff, but which can also provide secondary benefits of habitat enhancement/creation and active and passive recreational and educational opportunities.
- **Contaminant:** A substance that presents or has the potential to present a risk of harm to human health, the environment or any environmental value (Department of Environment and Conservation 2006).
- **Controlled groundwater level (CGL):** The controlled (i.e. modified) groundwater level (measured in metres Australian Height Datum) at which drainage inverts are set.
- **Conveyance systems:** A mechanism for transporting stormwater from one point to another, including swales, bioretention systems, living streams, pipes and channels.
- **Denitrification:** The reduction of nitrate or nitrite to nitrogen gas, in the absence of oxygen (ARMCANZ & ANZECC 2000).
- **Detention/detain:** The process of reducing the rate of off-site stormwater discharge by temporarily holding rainfall runoff (up to the design ARI event) and then releasing it slowly, to reduce the impact on downstream water bodies and to attenuate urban runoff peaks for flood protection of downstream areas.
- **Detention (ephemeral/dry) basins:** Areas, usually landscaped, formed by simple dam walls, by excavation below ground level or by utilisation or enhancement of natural swales or depressions, designed to temporarily detain stormwater to attenuate peak flows downstream to acceptable levels.

- **Detention time:** The theoretical time required to displace the contents of a stormwater treatment facility at a given rate of discharge (volume divided by rate of discharge).
- **Directly connected impervious surface:** An impervious surface connected directly to a receiving water body via a hydraulically efficient conveyance device (e.g. pipes or constructed drains/channels).
- **Discharge:** The rate at which a volume of water passes through a cross section in a unit of time (Water and Rivers Commission 2000b).
- **Dissolved fraction:** The part of a water sample passing through a 0.45 µm pore size filter paper. It will include both a truly dissolved and colloidal material fraction. (ARMCANZ & ANZECC 2000.)
- **Drainage network:** The system of channels and pipes and overland flow pathways which drain a catchment area (ARMCANZ & ANZECC 2000).
- **Drainage water:** Consists of stormwater runoff and/or shallow groundwater that has been intercepted by drains.
- **Ecological values:** Particular values or uses of the environment that are important for a healthy ecosystem or for public benefit, welfare, safety or health and economic activities, and which require protection from the effects of pollution, waste discharges and deposits (ARMCANZ & ANZECC 2000) and from the effects of altered water regimes.
- **Ecological water requirements (EWRs):** The water regimes needed to maintain ecological values of water dependent ecosystems at a low level of risk (Water and Rivers Commission 2000a). Also see 'environmental water provisions'.
- **Economic values:** Includes water body uses, stormwater use, economic values of the receiving environment (e.g. fishing and tourism), values of land used for stormwater management and values of land adjacent to stormwater management devices.
- **Education and participation program:** One of the five principal categories of non-structural BMPs for stormwater management. Examples include training programs and involving the community in the development and implementation of stormwater management plans.
- **Effective imperviousness:** The combined effect of the proportion of constructed impervious surfaces in the catchment, and the connectivity of these impervious surfaces to receiving water bodies (adapted from Walsh et al. 2004).
- **Effectiveness:** The extent to which project outcomes (see 'outcomes') are achieving project objectives (Bullen undated).
- **Efficiency:** The extent to which project outputs (see 'outputs') are maximised for the given level of inputs. Efficiency is concerned with the processes (activities/strategies/operations) by which the project is delivered and which produce the outputs of the projects. BMP Efficiency: Measures how well a BMP or BMP system removes or controls contaminants. Although 'percent removal' is the most common form of expressing BMP efficiency (when used alone), it is a poor measure of BMP efficiency compared with alternatives such as the 'effluent probability method'. (US EPA 2002; Taylor & Wong 2003.)
- **Effluent:** Sanitary, industrial or agricultural discharge from wastewater treatment plants or treatment lagoons (ARMCANZ & ANZECC 2000).
- **Environmental management systems (EMS):** The part of the overall management system that includes organisational structure, planning activities, responsibilities, practices, procedures, processes and resources for developing, implementing, achieving, reviewing and maintaining an environmental policy (Standards Australia 1996).
- **Environmental water provisions (EWPs):** The water regimes that are provided as a result of the water allocation decision-making process taking into account ecological, social and economic impacts. They may meet in part or in full the ecological water requirements. (Water and Rivers Commission 2000a.) See 'ecological water requirements'.
- **Erosion:** The process by which the land surface is detached and transported away by the action of water, wind, ice or gravity.

- **Evaluation:** A periodic but comprehensive assessment of the overall progress and worth of a project (Woodhill & Robins 1998). The term used for final assessment of whether a BMP has achieved its pre-defined objectives.
- **Event:** A single precipitation and associated runoff occurrence (ARMCANZ & ANZECC 2000).
- **Event mean concentration:** The average concentration of a contaminant over the period of an event discharge. It is normally determined by the sum of the concentrations (for multiple samples taken during the period of the event discharge) multiplied by the flow weighted volume of the sample, divided by the cumulative volume of the samples. (ARMCANZ & ANZECC 2000.)
- **Filter:** A layer of granular material designed to intercept fine particulate material. It may be used as part of a subsoil drain, or as a structure to treat surface runoff prior to recharge to groundwater or discharge to a drain. (ARMCANZ & ANZECC 2000.)
- **Filter strip:** See ‘buffer strip’.
- **First flush:** Describes situations when contaminants (e.g. sediments) that have accumulated on impervious surfaces are transported at the beginning of a rainfall event. This results in high pollution concentrations at the start of the runoff hydrograph, reducing to lower levels before the flood peak occurs. (Argue 2004.)
- **Flashiness:** Where water levels rapidly peak and decline.
- **Floodplain:** The portion of a waterway valley next to the channel which is covered with water when the waterway overflows its banks during major flow events (Water and Rivers Commission 2000c).
- **Freeboard:** The distance between the maximum water surface elevations anticipated in design and the top of retaining banks or structures. Freeboard is provided to prevent overtopping due to unforeseen conditions, and/or events greater than the maximum design event of the structure.
- **Frequency:** See ‘average recurrence interval’.
- **Geomorphology:** Of, or relating to, the forms of the earth’s surface and the processes associated with them (e.g. erosion, weathering, transport and deposition) (Water and Rivers Commission 2002).
- **Geotextile:** A thin, flexible permeable sheet of synthetic material used to allow the transmission of water through the pores of the material, while preventing the transmission of soil particles (ARMCANZ & ANZECC 2000).
- **Goals or aims:** General descriptions of what a project will achieve (Woodhill & Robins 1998).
- **Grain size distribution:** The statistical distribution of grain (by weight) passing a range of sieve sizes (ARMCANZ & ANZECC 2000).
- **Gravel:** A mixture of coarse mineral particles larger than 2 mm, but less than 75 mm in equivalent diameter (Charman & Murphy 1991).
- **Greenfield:** Land zoned for urban development and located on the fringe of an urban area (Western Australian Planning Commission 2004).
- **Gross pollutant traps (GPTs):** A type of litter and sediment management system. GPTs typically consist of a sediment trap with a weir and trash rack at the downstream end of a piped drainage system.
- **Groundwater:** Water found under the land surface that occupies pores and crevices of soil and rock (Water and Rivers Commission 2000a).
- **Gully pit/inlet pit/side entry pit:** A roadside inlet pit designed to collect stormwater runoff from paved surfaces and to intercept sediment and litter prior to entry into the drainage network (ARMCANZ & ANZECC 2000).
- **Heavy metals:** Metals of high specific gravity (>5 g/cm³) that are present in the environment from natural and anthropogenic sources such as municipal and industrial wastes and urban runoff, and pose long-term environmental hazards. Such metals include: arsenic (As), cadmium (Cd), chromium (Cr), cobalt (Co), copper (Cu), lead (Pb), mercury (Hg), molybdenum (Mo), nickel (Ni), vanadium (V) and zinc (Zn).
- **Hydraulic conductivity:** A measure of the ease of flow through a pore space or fractures. Hydraulic conductivity has units with dimensions of length per time (e.g. m/s, m/min, or m/d).

- **Hydraulic head:** The energy, either kinetic or potential, possessed by each unit weight of a liquid expressed as the vertical height through which a unit weight would have to fall to release the average energy possessed. Used in various terms such as pressure head, velocity head and head loss.
- **Hydrodynamic condition:** The condition that influences the flow of water.
- **Hydrologic regime:** A description of the variation of flow rate or water level over time (adapted from Water and Rivers Commission 2000a).
- **Hydrological cycle:** The continual cycle of water between the land, the ocean and the atmosphere.
- **Hydrology:** The science of the behaviour of water in the atmosphere, on the surface of the earth and within the soil and underlying rocks. This includes the relationship between rainfall, runoff, infiltration and evaporation.
- **Illicit connections:** Illegal or improper connections to drainage systems and receiving waters. The most obvious of these connections include trade wastes from commercial and industrial premises and wastewater from domestic premises.
- **Impermeable or impervious surface:** The part of the catchment surfaced with materials, either natural or constructed, which prevent or limit the rate of infiltration of stormwater into the underlying soil and groundwater (ARMCANZ & ANZECC 2000) and subsequently increases stormwater runoff flows.
- **Indicators:** The specific characteristics or phenomena that tell you about the project and what impact it is having on the problem or issue it was set up to tackle (Woodhill & Robins 1998).
- **Indirect drainage:** The breaking of the direct connection of stormwater pipes and impervious area runoff to the drainage network, by their discharge to pervious areas or infiltration devices.
- **Infiltration:** The movement of water from the surface to the subsoil and at times, ultimately to the underlying aquifer.
- **Infiltration system:** A drainage facility designed to use the hydrologic process of stormwater runoff soaking into the ground, commonly referred to as percolation. Examples include infiltration basins and trenches, soakwells and pervious paving.
- **Inlet:** A form of connection between the ground surface and a stormwater structural control for the admission of stormwater runoff.
- **Integrated water cycle management (IWCM):** The integration of water supply, sewerage and stormwater, so that water is used optimally within a catchment resource, State and national policy context. It promotes the coordinated planning, development and management of water, land and related resources (including energy use) that are linked to urban areas and the application of WSUD principles within the built urban environment. (National Water Commission 2006.)
- **Litter and sediment management (LSM) system:** Any structural device designed to intercept coarse particulate material (by sedimentation) and litter and debris (by physical screening). May also be referred to as a stormwater pollutant trap (SPT). Types of LSM systems include side entry pit traps, gross pollutant traps, trash racks and litter booms.
- **Living stream:** A drainage conveyance system featuring stabilised vegetated banks and a more natural morphology than traditional straight drains, providing diverse habitats for native plants and animals.
- **Loading:** The total mass of a contaminant discharged during a storm event. The term may also be used to describe the mass of contaminant intercepted (g/m^2) by a device during a storm event, or on an annual basis. (ARMCANZ & ANZECC 2000.)
- **Managed aquifer recharge (MAR):** The controlled infiltration or injection of water into an aquifer. The water can be withdrawn at a later date, left in the aquifer for environmental benefits, or used as a barrier to prevent saltwater or other contaminants from entering the aquifer.
- **Monitoring:** The collection of data by various methods for the purpose of understanding natural systems and features, evaluating the impacts of development proposals on such systems, and assessing the performance of mitigation measures.
- **Monitoring and evaluation program:** Development of monitoring and evaluation activities to determine the success or otherwise of measures put in place as part of stormwater management projects.

- **Multiple use corridors:** Facilities performing a range of functions (e.g. stormwater management, landscape, recreation and wildlife habitat).
- **Non-point source pollution:** Pollution from diffuse sources without a single point of origin or specific discharge point (ARMCANZ & ANZECC 2000).
- **Non-structural controls:** Institutional and pollution-prevention practices designed to prevent or minimise contaminants from entering stormwater runoff and/or reduce the volume of stormwater requiring management (US EPA 1999). They do not involve fixed, permanent facilities and they usually work by changing behaviour through government regulation (e.g. planning and environmental laws), education and/or economic instruments (Taylor & Wong 2002).
- **Nutrients:** Essential chemicals such as nitrogen (N) and phosphorus (P) needed by plants and animals for growth. Excessive amounts of nutrients can lead to degradation of water quality and algal blooms.
- **Objectives:** Specific statements about what a project intends to achieve.
- **Offline:** A management system located adjacent to but off a stream or major flow pathway, such as to treat low flows or the discharge of a major flow system (ARMCANZ & ANZECC 2000).
- **Oil trap/separators:** A stilling tank configured to separate lighter oily matter, scums and hydrocarbons from stormwater.
- **Online:** A management system located within the original stream or flow pathway/drainage channel to treat event flows (ARMCANZ & ANZECC 2000).
- **On-site and off-site:** On-site facilities are located on individual lots to enhance local stormwater retention/detention and interception of contaminants. Off-site facilities are located on stormwater networks to provide area-wide stormwater retention/detention and interception of contaminants. (Adapted from ARMCANZ & ANZECC 2000.)
- **Outcomes:** The results of the activities or products of a project (Woodhill & Robins 1998). All the impacts or consequences of the project beyond its outputs (see 'outputs'). Outcomes are often delayed or long term and they may be intended or unanticipated (Bullen undated).
- **Outlet:** Point of water discharge from a waterway or stormwater structural control.
- **Outputs:** The activities completed or products made during a project (Woodhill & Robins 1998). Outputs are within the direct control of the project.
- **Overland flow:** The component of rainfall (excess) that is not removed by infiltration or use and discharges down-gradient as surface flow (ARMCANZ & ANZECC 2000).
- **Peak discharge rate:** The maximum instantaneous rate of flow during a storm, usually in reference to a specific design storm event.
- **Peak flow:** Maximum flow rate in a flood, measured in m³/s (Department of Environment 2003).
- **Performance indicator:** A specific type of indicator that looks at outcomes (see 'outcomes') to see if they are meeting the project's objectives (see 'objectives').
- **Performance monitoring:** Gathering of information to measure the success of strategies implemented when compared to objectives (see 'objectives').
- **Permeable soils:** Soil materials with sufficiently rapid infiltration rate, therefore reducing or eliminating stormwater runoff. Coarse textured soils tend to have large, well-connected pore spaces and hence high permeability.
- **Pervious (permeable/porous) pavement:** Pavements comprising materials that facilitate stormwater infiltration and transfer to the underlying subsoil (ARMCANZ & ANZECC 2000).
- **pH:** A measure of the hydrogen ion concentration of water or wastewater; expressed as the negative log of the hydrogen ion concentration [H⁺]. A pH of 7 is neutral, pH less than 7 is acidic and pH greater than 7 is basic.
- **Point source pollution:** Contamination from a localised source, such as leaky storage tanks and drums or sewage discharge.
- **Pollutant retention:** The proportion of pollutant load intercepted and retained by a device, either on an event or annual basis (ARMCANZ & ANZECC 2000).

- **Pollution prevention procedures:** One of the five principal categories of non-structural BMPs for stormwater management. Examples include maintenance practices (e.g. maintenance of the stormwater drainage network) and elements of environmental management systems (e.g. procedures on material storage and staff training on stormwater management at government, commercial and industrial sites).
- **Porosity:** Porosity is calculated as a ratio of pore volume to total volume.
- **Potable water:** Water generally considered suitable for human consumption.
- **Precautionary principle:** If there are threats of serious or irreversible environmental damage, lack of full scientific certainty should not be used as a reason for postponing measures to prevent environmental degradation.
- **Rational method:** A means of computing storm drainage flow rates (Q) by use of the formula $Q = CIA$, where C is a coefficient describing the physical drainage area, I is the rainfall intensity and A is the area.
- **Receiving environment:** Areas that receive stormwater runoff, including wetlands, waterways, coastal waters/dunes, groundwater and bushland areas.
- **Receiving water bodies:** Include waterways, wetlands, coastal marine areas and shallow groundwater aquifers.
- **Recharge:** Water infiltrating to replenish an aquifer.
- **Recycled water:** Treated stormwater, greywater or black water suitable for a range of uses, e.g. toilet flushing, irrigation, industrial processing or other suitable applications (ARMCANZ & ANZECC 2000).
- **Regulatory controls:** One of the five principal categories of non-structural BMPs for stormwater management. Includes controls such as enforcement of local laws to improve erosion and sediment control on building sites, the use of regulatory instruments such as environmental licences to help manage premises likely to contaminate stormwater or groundwater, and programs to minimise illicit discharges to stormwater management systems (e.g. drains).
- **Remobilisation:** The transformation of sedimented contaminants by microbial or chemical processes into a dissolved form and transfer by diffusion from the sediment pore water into the water column (ARMCANZ & ANZECC 2000).
- **Re-suspension:** The physical entrainment of sedimented particles by elevated flows, or as a result of sediment bio-turbation (ARMCANZ & ANZECC 2000).
- **Retention/retain:** Retention is defined as the process of preventing rainfall runoff from being discharged into receiving water bodies by holding it in a storage area. The water may then infiltrate into groundwater, evaporate or be removed by evapotranspiration of vegetation. Retention systems are designed to prevent off-site discharges of surface water runoff, up to the design ARI event. It is the difference between total precipitation and total runoff.
- **Retrofitting:** Retrofitting employs additional or alternative stormwater management devices or approaches which are installed or undertaken in an existing developed area. Retrofitting can occur at the lot, block/neighbourhood or catchment scale.
- **Riffles:** High points in the channel floor, representing bedrock bars or accumulations of relatively coarse material. Water flow is typically relatively shallow, fast and rough over riffles. (Water and Rivers Commission 2002.)
- **Riparian vegetation:** Vegetation growing within the channel and the along banks of waterways, extending laterally away from the bank and ending at the extent of the floodplain.
- **Riprap:** Rock riprap consists of a layer or layers of well-graded rocks placed on stream banks to protect them from erosion.
- **Risk:** The chances of something happening that will have an impact on objectives. It is measured in terms of consequences and likelihood. (Standards Association of Australia 1999.)
- **Risk assessment:** The process of risk analysis and risk evaluation.
- **Roughness coefficient:** A factor in velocity and discharge formulas representing the effect of channel roughness on energy losses in flowing water. Manning's n is a commonly used roughness coefficient.

- **Runoff:** Water that flows over the surface of a catchment area, including streams.
- **Sand:** A soil separate consisting of particles between 0.02 and 2.0 mm in equivalent diameter. Fine sand is defined as particles between 0.02 and 0.2 mm, and coarse sand as those between 0.2 and 2.0 mm. (Charman & Murphy 1991.)
- **Sediment:** Solid fragment of organic and inorganic material that is transported, suspended and/or deposited by water and wind.
- **Sedimentation:** The physical process of settling of suspended particulates under the force of gravity (ARMCANZ & ANZECC 2000).
- **Sediment trap:** A structure designed to intercept and retain sediment transported by water flow (ARMCANZ & ANZECC 2000).
- **Silt:** A soil separate consisting of particles between 0.002 and 0.02 mm in equivalent diameter (Charman & Murphy 1991).
- **Social/cultural values:** Social values include public health and safety, recreational uses and visual amenity. Cultural values include historical and spiritual significance, and scientific and educational uses.
- **Sodic soils:** Soil sodicity is assessed by the ratings of the exchangeable sodium percentage (ESP). Soils with a relatively high proportion of exchangeable sodium (greater than 6 per cent) are considered sodic (Charman & Murphy 1991). Soil sodicity causes increased soil dispersion and swelling of clays, which adversely impacts the soil structure and results in reduced infiltration, reduced hydraulic conductivity and the formation of surface crusts.
- **Soil amendment:** Involves adding an agent, such as clay or crushed limestone, to the soil to improve its structure, porosity, water holding capacity and nutrient recycling capacity.
- **Soil permeability:** The ease with which gases, liquids or plant roots penetrate or pass through a layer of soil.
- **Soil stabilisation:** The use of measures or materials, such as rock lining or vegetation, to prevent the movement of soil when loads are applied to the soil.
- **Source controls:** Non-structural or structural best management practices designed to minimise the generation of excessive stormwater runoff and/or pollution of stormwater at or near the source and protect receiving environments.
- **Stormwater:** Water flowing over ground surfaces and in natural streams and drains, as a direct result of rainfall over a catchment. Stormwater consists of rainfall runoff and any material (soluble or insoluble) mobilised in its path of flow.
- **Stormwater quality:** The chemical, physical and biological characteristics of stormwater.
- **Stormwater quantity:** The volume characteristics of stormwater.
- **Strategic planning and institutional controls:** One of the five principal categories of non-structural BMPs for stormwater management. Examples include controls such as the use of strategic, regional or citywide urban stormwater management plans and stable funding arrangements to support the implementation of these plans.
- **Street sweeping:** The removal of particulates and litter from street surfaces by sweeping or vacuuming (ARMCANZ & ANZECC 2000).
- **Structural controls:** Engineered devices implemented to manage runoff quality and quantity, to control, treat, or prevent stormwater pollution and/or reduce the volume of stormwater requiring management.
- **Sub-catchment:** A topographically defined area drained by a tributary of a primary stream (ARMCANZ & ANZECC 2000).
- **Subsurface drain:** A drain designed to intercept subsoil water and thereby limit the seasonal maximum groundwater level.
- **Superficial (unconfined) aquifer:** An aquifer containing water with no upper non-porous layer to limit its volume or to exert pressure. The upper surface of the groundwater within the aquifer is called the watertable.

- **Surface water:** Water flowing or held in waterways or wetlands on the surface of the landscape (adapted from Water and Rivers Commission 2000a).
- **Suspended solids:** Organic or inorganic particles that are suspended and transported by water. This includes sand, mud and clay particles (and associated contaminants) in stormwater.
- **Swale:** A drainage interception and conveyance system with relatively gentle side slopes and shallow flow depths.
- **Target:** A numerical concentration limit or descriptive statement relating to an aspect of water management aspired to as part of a stormwater management project.
- **Time of concentration:** The time required for a drop of water to travel from the most hydrologically remote point to the point of discharge.
- **Threat:** An activity or land use with potential to damage the local or receiving environment's social/cultural, ecological or economic values, via impacts to stormwater quantity or quality.
- **Total phosphorus (TP):** The total phosphorus that is contained within the matrix.
- **Total suspended solids (TSS):** A water quality measurement referring to the dry-weight of particles in a sample that is trapped by a filter of specified pore size.
- **Town planning controls:** One of the five principal categories of non-structural BMPs for stormwater management. An example includes the use of town planning instruments to promote water sensitive urban design features in new developments.
- **Toxicity:** The quantity or degree to which a substance is poisonous or harmful to plant, animal or human health.
- **Treatment train:** In most situations, a number of management measures may be implemented in series or concurrently forming a treatment train approach to stormwater management. To achieve the best stormwater management outcomes, both structural and non-structural techniques should be used in particular combinations to suit the local conditions. This arrangement will satisfy the water quantity and quality objectives that might be unachievable if relying on a single BMP. Additionally, the impact from the failure of one device will be reduced by the operation of the other devices in the treatment train.
- **Triple-bottom-line assessment:** A process which uses multi-criteria analysis to evaluate the economic, social and ecological costs and benefits of possible BMPs.
- **Underdrain:** Plastic pipes with holes, installed at the base of impervious bioretention systems to collect treated water for conveyance downstream.
- **Urban:** Land used for residential, rural-residential, commercial or industrial development (includes regional towns).
- **Values:** Values may include economic values (e.g. water use, aquaculture and stormwater reuse), ecological values (e.g. aquatic fauna and flora, urban bushland) and social/cultural values (e.g. historical, public health and safety, recreational, visual amenity, spiritual).
- **Vegetated swales:** A swale with vegetation covering the side slopes and base. Vegetation can range from grass to native sedges and shrubs, depending on hydraulic and landscape requirements.
- **Water bodies:** Waterways, wetlands, coastal marine areas and shallow groundwater aquifers.
- **Watercourses:** A river, stream or creek in which water flows in a natural channel, whether permanently or intermittently.
- **Water dependent ecosystems:** Those parts of the environment, the species composition and natural ecological processes of which are determined by the permanent or temporary presence of water resources, including flowing or standing water and water within groundwater aquifers (Water and Rivers Commission 2000a).
- **Water sensitive urban design (WSUD):** A design philosophy that provides a framework for managing water-related issues in urban areas. WSUD incorporates the sustainable management and integration of stormwater, wastewater and water supply into urban design. WSUD principles include incorporating water resource management issues early in the land use planning process. WSUD can be applied at the lot, street, neighbourhood, catchment and regional scale.

- **Waterways:** All seasonal, intermittent or permanent streams, creeks, rivers, estuaries, coastal lagoons, inlets and harbours.
- **Wetlands:** Areas of seasonally, intermittently or permanently waterlogged or inundated land, whether natural or otherwise, including lakes, sumplands, playas, damplands, floodplains, barlkarras, palusplains, paluslopes, palusmonts or tidal flats.

3 Contacts

Department of Water:

For stormwater management policy/guideline information, contact the Drainage and Waterways Branch, Department of Water. Phone: 6364 7600. Address: The Atrium, Level 4, 168 St Georges Terrace, Perth WA 6000. Mail: PO Box K822, Perth WA 6842. Department of Water Stormwater web page: <<http://stormwater.water.wa.gov.au>>.

For local water management advice and assessment, contact the regional office of the Department of Water. For the most up to date regional contact details, go to the Contacts tab on the Department of Water website: <<http://www.water.wa.gov.au>>.

New Water Ways capacity building program:

For information about the new integrated water cycle management capacity building program for Western Australia 'New Water Ways', contact the New Water Ways Project Manager, c/- Western Australian Local Government Association (WALGA). Phone: 9213 2033. Address: 15 Altona St, West Perth WA 6005. Mail: PO Box 1544, West Perth WA 6872.

4 Websites

Australian Water Association (AWA) website: <<http://www.awa.asn.au>>.

Bureau of Meteorology website: <<http://www.bom.gov.au>>.

Bush Forever web page via the Western Australian Planning Commission's website: <<http://www.wapc.wa.gov.au>>, search for Bush Forever.

Conservation Council of Western Australia Inc. website: <<http://www.conservationwa.asn.au>>.

Department of Agriculture website: <<http://www.agric.wa.gov.au>>.

Department of Environment and Conservation (DEC) website: <<http://www.dec.wa.gov.au>>.

Department of Environment and Conservation's Florabase website: <<http://florabase.dec.wa.gov.au>>.

Department of Health's Environmental Health website: <<http://www.health.wa.gov.au/envirohealth/home/index.cfm>>.

Department of Indigenous Affairs (DIA) website: <<http://www.dia.wa.gov.au/Heritage>>.

Department of Water (DoW) website: <<http://www.water.wa.gov.au>>.

Department of Water's stormwater web page: <<http://stormwater.water.wa.gov.au>>.

Department for Planning and Infrastructure (DPI) website: <<http://www.dpi.wa.gov.au>>.

Environmental Protection Authority (EPA) website: <<http://www.epa.wa.gov.au>>.

Landgate (formerly Department of Land Information) website: <<http://www.landgate.wa.gov.au>>.

Housing Industry Association (HIA) website: <<http://www.hia.com.au>>.

ICLEI Local Governments for Sustainability Australia/New Zealand website for information about the WA Water Campaign: <<http://www.iclei.org/anz>>.

Institution of Engineers Australia (Engineers Australia) website: <<http://www.engineersaustralia.org.au>>.

Institute of Public Works Engineering Australia (IPWEA) website: <<http://www.engineersaustralia.org.au>>.

Main Roads Western Australia website: <<http://www.mainroads.wa.gov.au>>.

Midge Research Group: <<http://www.cockburn.wa.gov.au/midges/index.html>>.

Natural resource management (NRM) councils' websites:

- Avon Catchment Council: <<http://www.avoncm.org.au>>
- Northern Agricultural Catchments Council (NACC): <<http://www.nacc.com.au>>
- Rangelands NRM Co-ordinating Group: <<http://www.rangelandswa.info>>
- South Coast Regional Initiative Planning Team (SCRIPT): <<http://www.script.asn.au>>
- South West Catchments Council (SWCC): <<http://www.swcatchmentscouncil.com>>
- Swan Catchment Council: <<http://www.wrc.wa.gov.au/swanavon/pages/council.html>>

Shared Land Information Platform (SLIP) website: <<https://www2.landgate.wa.gov.au/slip/portal/home/home.html>>.

Stormwater Industry Association (SIA) Inc. website: <<http://www.stormwater.asn.au>>.

Swan River Trust website: <<http://www.swanrivertrust.wa.gov.au>>.

Urban Development Institute of Australia (UDIA), Western Australia Division Incorporated website: <<http://www.udiawa.com.au>>.

Urbanwater.info website: <<http://www.urbanwater.info>>.

Water Corporation website: <<http://www.watercorporation.com.au>>.

Western Australian Land Information System (WALIS) website: <<http://www.walis.wa.gov.au>> for general queries about spatial information.

Western Australian Local Government Association (WALGA) website: <<http://www.walga.asn.au>>.

Western Australian Museum website: <<http://www.museum.wa.gov.au>>.

Western Australian Museum's Faunabase website: <<http://www.museum.wa.gov.au/faunabase>>.

Western Australian Planning Commission website: <<http://www.wapc.wa.gov.au>>.

5 Glossary references

- Agriculture and Resource Management Council of Australia and New Zealand (ARMCANZ) and Australian and New Zealand Environment and Conservation Council (ANZECC) 2000, National Water Quality Management Strategy No. 10, *Australian Guidelines for Urban Stormwater Management*, ANZECC, Canberra, Australian Capital Territory.
- Argue, J. R. (ed.) 2004, *Water Sensitive Urban Design: Basic Procedures for 'Source Control' of Stormwater – a handbook for Australian practice*, Urban Water Resources Centre, University of South Australia, Adelaide, South Australia.
- Bullen, P. undated, *Management Alternatives for Human Services*, Management Alternatives Pty Ltd. Available via <<http://www.mapl.com.au/index.htm>> (sourced on 11 April 2005).
- Charman, P. E. V. and Murphy, B. W. (eds.) 1991, *Soils – Their Properties and Management: a soil conservation handbook for New South Wales*, Sydney University Press in association with Oxford University Press, South Melbourne, Victoria.
- Department of Environment 2003, *Stream and Catchment Hydrology*, River Restoration Report No. RR19, Department of Environment, Perth, Western Australia.
- Department of Environment 2004, *Draft Setting Targets for the Swan-Canning: context, existing targets and future directions*, Unpublished report, Department of Environment, Perth, Western Australia.
- Department of Environment and Conservation 2006, *The Use of Risk Assessment in Contaminated Site Assessment and Management*, Contaminated Sites Management Series, Department of Environment and Conservation, Perth, Western Australia.
- National Water Commission 2006, *Review of Institutional and Regulatory Models for Integrated Urban Water Cycle Management*, Draft issues and scoping paper, Canberra, Australian Capital Territory.
- Standards Australia 1996, *Environmental Management Systems – Specification with Guidance for Use*, AS/NZS 14001:1996, Standards Australia, Sydney, New South Wales. Available via <<http://www.standards.com.au>>.
- Standards Association of Australia 1999, *Australian/New Zealand Standard: Risk Management*, AS/NZS 4360:1999, Standards Association of Australia, Canberra, Australian Capital Territory.
- Taylor, A. C. and Wong, T. H. F. 2002, *Non-Structural Stormwater Quality Best Management Practices: an overview of their use, value, cost and evaluation*, Technical Report No. 02/11, Cooperative Research Centre for Catchment Hydrology, Melbourne, Victoria. Available via <<http://www.catchment.crc.org.au/pdfs/technical200211.pdf>>.
- Taylor, A. C. and Wong, T. H. F. 2003, *Non-structural Stormwater Quality Best Management Practices: guidelines for monitoring and evaluation*, Technical Report 03/13, Cooperative Research Centre for Catchment Hydrology, Melbourne, Victoria.
- United States Environmental Protection Agency (US EPA) 1999, *Preliminary Data Summary of Urban Stormwater Best Management Practices*, United States Environmental Protection Agency, Washington, United States of America. Available via <<http://www.epa.gov/waterscience/guide/stormwater>>.
- United States Environmental Protection Agency (US EPA) 2002, *Urban Stormwater BMP Performance Monitoring, a guidance manual for meeting the National Stormwater BMP Database requirements*, United States Environmental Protection Agency and American Society of Civil Engineers, United States of America. Available via <<http://www.BMPdatabase.org/index.htm>>.

- Walsh, C. J., Leonard, A. W., Ladson, A. R. and Fletcher, T. D. 2004, *Urban Stormwater and the Ecology of Streams*, Cooperative Research Centre for Freshwater Ecology and Cooperative Research Centre for Catchment Hydrology, Canberra, Australian Capital Territory.
- Water and Rivers Commission 2000a, *Environmental Water Provisions Policy for Western Australia*, Statewide Policy No. 5, Water and Rivers Commission, Perth, Western Australia.
- Water and Rivers Commission 2000b, *Stream Channel Processes: fluvial geomorphology*, River Restoration Report No. RR6, Water and Rivers Commission, Perth, Western Australia.
- Water and Rivers Commission 2000c, *Floodplain Management*, Water Facts No. 14, Water and Rivers Commission, Perth, Western Australia.
- Water and Rivers Commission 2001, *Stream Stabilisation*, River Restoration Report No. RR10, Water and Rivers Commission, Perth, Western Australia.
- Water and Rivers Commission 2002, *Recognising Channel and Floodplain Forms*, River Restoration Report No. RR17, Water and Rivers Commission, Perth, Western Australia.
- Western Australian Planning Commission 2004, *Liveable Neighbourhoods*, Edition 3 draft for public comment, Western Australian Planning Commission, Perth, Western Australia.
- Woodhill, J. and Robins, L. 1998, *Participatory Evaluation for Landcare and Catchment Groups – a guide for facilitators*, Greening Australia, Canberra, Australian Capital Territory.

6 Further reading

- Agriculture and Resource Management Council of Australia and New Zealand (ARMCANZ) and Australian and New Zealand Environment and Conservation Council (ANZECC) 2000, National Water Quality Management Strategy No. 10: *Australian Guidelines for Urban Stormwater Management*, ANZECC, Canberra, Australian Capital Territory.
- Department of Environment and Conservation (in preparation), *A Guide to Managing and Restoring Wetlands in Western Australia*, Department of Environment and Conservation, Perth, Western Australia.
- Department of Environment and Swan River Trust 2005, *Decision Process for Stormwater Management in WA*, Department of Environment and Swan River Trust, Perth, Western Australia. Available via <<http://stormwater.water.wa.gov.au>>.
- Department of Water 2007, *Interim Drainage and Water Management Position Statement: Constructed Lakes*, Department of Water, Perth, Western Australia. Available via <<http://stormwater.water.wa.gov.au>>.
- Engineers Australia 2006, *Australian Runoff Quality – a guide to water sensitive urban design*, Wong, T. H. F. (Editor-in-Chief), Engineers Media, Crows Nest, New South Wales.
- Environmental Protection Authority 2005, *Environmental Guidance for Planning and Development*, Draft Guidance Statement No. 33, Environmental Protection Authority, Perth, Western Australia. Available via <<http://www.epa.wa.gov.au>>.
- Institution of Engineers Australia 2001, *Australian Rainfall and Runoff – a guide to flood estimation* (Revised Edition), D. H. Pilgrim (ed.), Institution of Engineers Australia, Melbourne, Victoria.

Water and Rivers Commission/Department of Environment 1999 – 2003, *River Restoration Manual: a guide to the nature, protection, rehabilitation and long-term management of waterways in Western Australia*, Water and Rivers Commission/Department of Environment, Perth, Western Australia. Available via <<http://www.water.wa.gov.au>>, go to Water Management/Waterways/River Restoration.

Western Australian Planning Commission 2004, *Liveable Neighbourhoods*, Edition 3 draft for public comment, Western Australian Planning Commission, Perth, Western Australia. Available via <<http://www.wapc.wa.gov.au/Publications>>.

Government of Western Australia 2006, State Planning Policy 2.9, *Water Resources*, State Law Publisher, Perth, Western Australia. Available via <<http://www.wapc.wa.gov.au/Publications>>.

7 Acronyms

ANZECC	Australian and New Zealand Environment and Conservation Council
ARI	Average recurrence interval
ARMCANZ	Agriculture and Resource Management Council of Australia and New Zealand
ARQ	Australian Runoff Quality
ARR	Australian Rainfall and Runoff
ASS	Acid sulphate soils
ASR	Aquifer storage and recovery
BOD	Biochemical oxygen demand
BMP	Best management practice
CGL	Controlled groundwater level
DIA	Department of Indigenous Affairs
DEC	Department of Environment and Conservation
DoW	Department of Water
DPI	Department for Planning and Infrastructure
DWMS	Drainage and water management strategy
EMS	Environmental management system
EPA	Environmental Protection Authority
EWP	Environmental water provision
EWR	Ecological water requirement
GIS	Geographic information system
GPT	Gross pollutant trap
IWCM	Integrated water cycle management

LSM	Litter and sediment management
MAR	Managed aquifer recharge
NRM	Natural resource management
POS	Public open space
PRI	Phosphorus retention index
SMP	Stormwater management plan
SPT	Stormwater pollutant trap
TDS	Total dissolved solids
TN	Total nitrogen
TP	Total phosphorus
TSS	Total suspended solids
UWMP	Urban water management plan
WALGA	Western Australian Local Government Association
WALIS	Western Australian Land Information System
WAPC	Western Australian Planning Commission
WIN	Water Information Network
WSUD	Water sensitive urban design